

PASSHOT CCNP/CCIE(350-601)DCCOR

Number: 350-601

Passing Score: 825

Time Limit: 140 min

Follow us to learn more!

Whatsapp/Skype: +86 13559033962

Facebook: Passhot Club

Twitter: passhot1

QUESTION 1

A customer has a requirement to deploy a cloud service and needs to have full control over the underlying OS, data and applications. Which cloud model meets this requirement?

- A. PaaS
- B. MaaS
- C. SaaS
- D. IaaS

Answer: D

QUESTION 2

APIC EPG Resolution Immediacy is set to "Immediate". Which statement is true about the Deployment Immediacy for VMM domains associated to EPGs?

- A. If "On demand" is selected, the policy is programmed in the hardware only when the APIC detects a VM created in the EPG.
- B. If "Immediate" is selected, the policy is programmed in the hardware as soon as the leaf is booted.
- C. The "Immediate" and "On demand" options require a port group to be created on the VDS.
- D. If "On demand" is selected, the policy is programmed in the hardware only when the first packet is received through the data path.

Answer: A

QUESTION 3

An engineer is implementing an import operation in Cisco UCS Manager. What is the impact of performing this operation?

- A. Information can be modified on the management plane only.
- B. A configuration can be imported from a higher release to a lower release.
- C. Only a configuration file that was exported from the same Cisco UCS Manager can be imported.
- D. An import operation can be scheduled.

Answer: A

QUESTION 4

Which command reduces the amount of time it takes to complete the ISSU on a Cisco Nexus 7000 Series Switch that has dual supervisor modules and two I/O modules?

- A. install all epId bootflash: parallel
- B. install all epId bootflash:
- C. install all kickstart system
- D. install all kickstart system parallel

Answer: D

QUESTION 5

Which statement is true about upgrading the firmware on a Cisco MDS storage switch with dual supervisors?

- A. Supervisors can be upgraded independently to test the new firmware.
- B. Both supervisors load the new firmware and then the active supervisor reboots.
- C. The new firmware is loaded on the standby supervisor first.
- D. The standby supervisor must be offline before the firmware upgrade begins.

Answer: C